

Polywater®

CPL

Pourable Lubricant


Universal Pulling Lubricant

for Fiber Optic, Copper,

Coax, and Power

Supply Cables

- Superior friction reduction! -



***Also Available in
WINTERGRADE
(Non-Freezing) Formula**

- Pourable lubricant for easy underground application
- Compatible with all cable jackets, including polyethylene
- Effective lubrication when dry
- Lubricates cable for long distance-liquid clings to cable

Polywater® Cable Lubricant CPL

Polywater® Lubricant CPL is a universal high performance, pourable cable pulling lubricant formulated specifically for the communications industry. It is recommended for long fiber optic, copper, coaxial, or power supply cable pulls.

Polywater® Lubricant CPL provides maximum friction reduction between cable and conduit under both low and high sidewall bearing pressures. It is slow-drying and leaves a lubricating film after its water base has evaporated. Polywater® CPL is a stringy, silicone-enhanced lubricant that clings to cable throughout a pull. This cling maximizes surface area lubrication, thus increasing the efficiency of the cable pull.

Cat. No.	Pack. Size	Case Qty
CPL-128	1-gal (3.8 liter) jug	4
CPL-320	2.5-gal (9.5 liter) jug	2
CPL-640	5-gal (18.9 liter) pail	1

Winter Grade Cat. No.	Pack. Size	Case Qty
WCPL-35	1-quart (0.95 liter) bottle	12
WCPL-128	1-gal (3.8 liter) jug	4
WCPL-320	2.5-gal (9.5 liter) jug	2
WCPL-640	5-gal (18.9 liter) pail	1

Polywater® Lubricant CPL meets California Environmental Regulation CCR 22-Flathead minnow hazardous waste bioassay. Polywater® CPL is suitable for use on PE communication cable jackets.

SPECIFICATIONS

- Lubricity:** LDPE-, MDPE- and HDPE jacketed cable on HDPE and PVC innerduct at 200 lbs./ft. (2.91 kN/m) sidewall force, coefficient of kinetic friction < 0.12
- Percent non-volatile solids:** 4.5% to 5.5%
- Appearance:** Opaque-white stringy liquid. Pourable viscosity (1,000-3,000 cps@10rpm)
- Temperature use range:** 20°F to 120°F (-5°C to 50°C) for Polywater® CPL, -20°F to 120°F (-30°C to 50°C) for Polywater® CPL.
- pH:** Neutral (6.5-7.5).
- Cable compatibility:** No deleterious effects on physical or electrical properties of cable jackets.
- Polyethylene stress cracking:** No stress cracking on LDPE cable jackets when tested by ASTM D1693.
- Temperature stability:** No more than a 20% change in Brookfield viscosity from 40°F to 100°F (5°C to 40°C). No phase-out after five freeze/thaw cycles or 5-day exposure at 120°F (50°C).
- Toxicity:** Non-toxic and non-sensitizing. Industrial use only.
- Flammability:** Lubricant has no flash point and dried residue is not combustible.
- Clean-up:** Complete clean-up possible with water.

To view technical information on our website go to:

General Cable Lubricant information: www.polywater.com/lubeinfo.asp

Installing Communication Cable in Conduit: www.polywater.com/commcabl.html

Duct Factor in F/O Pulling: www.polywater.com/ductdisp.html



phone: 1-800-328-9384

1-651-430-2270

fax: 1-651-430-3634

email: support@polywater.com

11222 60th Street North, Stillwater, MN 55082, U.S.A.

ADHESIVES | CLEANERS | **LUBRICANTS** | SEALANTS

WWW.POLYWATER.COM

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.