Revision Date: January 2, 2015 Revision Number: 4

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

## 1.1 Product identifier

# Product Name: CableFree<sup>®</sup> Loosener

Product ID numbers: CF-35, CF-35C, CF-128, CF-640

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses:Cable removalList of advices against:Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

Polywater Europe BV

Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen

Netherlands

Tel: +31 (0)10 2330578 Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

## 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Flammable Liquid, Cat 4, H227 Skin Sensitivity, Cat 1, H317 Eye Irritation, Cat 2, H319

#### 2.2 Label elements

**Contains:** Petroleum distallates, hydrotreated light; d-Limonene, Ethoxylated alcohols



**Pictograms:** 

Signal word: Warning

**Hazard Statements:** 

H227 Combustible liquid

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

**Precautionary Statements:** 

P210 Keep away from flames and hot surfaces. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

P338 if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide to extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local regulations.

**2.3 Other hazards:** No information available.

## 3. Composition/Information on Ingredients

Component	CAS#	EC#	Wt. %	<b>GHS/CLP Classification</b>
				Asp. Tox. 1 H304;
				EUH066
Petroleum distillates,				Skin Irrit. 3 H316;
hydrotreated light	64742-47-8	265-149-8	< 10	Flam Liq 4 H227
				Skin Irrit. 2 H315;
				Skin Sens 1 H317;
				Flam Liq 3 H226;
				Aquatic Tox Acute 1, H400;
d-Limonene	5989-27-5	227-813-5	< 10	Aquatic Tox Chronic 1, H410
Ethoxylated alcohols	68439-46-3	500-446-0	< 3	Eye Dam 1, H318

## 4. First Aid Measures

#### 4.1 Description of first aid measures

**Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes

with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

**Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation

occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth. If victim is drowsy or

unconscious, place on the left side with head down. Do not leave victim

unattended. Seek medical attention.

## 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

# 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

## 5. Firefighting Measures

## 5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

## 5.2 Special hazards arising from the substance or mixture

## Hazardous decomposition and by-products:

Burning generates CO, CO<sub>2</sub> and smoke. Smoke may be acrid and fumes irritating.

## 5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

## 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use only non-sparking tools to clean up the spill. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Work gloves that are resistant to aromatic hydrocarbons are recommended. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

## 6.2 Environmental precautions:

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

## 6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

#### 6.4 Reference to other sections:

Refer to Sections 4. 5. 8. and 13 for more information.

## 7. Handling and Storage

## 7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

#### 7.3 Specific end uses

See flyer on this product for further information.

# 8. Exposure Controls / Personal Protection

# 8.1 Control parameters

## **Exposure limits and recommendations:**

Component Name	Limit	Standard	Source/Note
Petroleum distillates, hydrotreated light	100 ppm	ACGIH TWA	United States
Petroleum distillates, hydrotreated light	500 ppm	OSHA TWA	United States
Petroleum distillates, hydrotreated light	1200 mg/m3	RCP* TWA	ACGIH, Manufacturer

<sup>\*</sup>reciprocal calculation procedure for total hydrocarbons

## 8.2 Exposure controls

## **Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

# **Protective gloves:**

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

## Eye protection:

Safety glasses recommended.

## Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

## 9. Physical and Chemical

## 9.1 Information of basic physical and chemical properties

**Appearance:** Milky white, stringy liquid with light citrus odor.

Odor threshold:

pH:

Not available

Not available

Not available

**Boiling point:** I.B.P. 212°F / 100°C

Flash point: 167°F (75°C), Closed Cup (PMCC)

**Evaporation rate:** <0.1 (n-butyl acetate = 1) **Flammability (solid, gas):** Not applicable to liquids

Upper/lower flammability or

explosive limits:Not availableVapor pressure:Not availableVapor density (Air = 1):Not available

Specific gravity ( $H_2O = 1$ ): 0.98 Solubility in water: >80%

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not available

**Viscosity:** 1,500 – 5,000 cps. @ 10 rpm.

9.2 Other Information

**Volatiles (Weight %):** 93-94% **VOC Content:** 152 g/l

# 10. Stability and Reactivity

## 10.1 Reactivity:

See remaining headings in Section 10.

# 10.2 Chemical stability:

Stable

## 10.3 Possibility of hazardous reactions:

None known.

#### 10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

# 10.5 Incompatible materials :

Strong oxidizing agents.

## 10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

## 11. Toxicological Information

## 11.1 Information on toxicological effects:

## **Acute toxicity**

## Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

## Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

#### **Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes. It may cause an allergic skin reaction.

## Inhalation (Breathing):

Vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

## Ingestion:

Material has low level of oral toxicity. Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

## **Toxicity to Animals:**

Petroleum distillates,

hydrotreated light: LD<sub>50</sub> (oral rat) >5000 mg/kg

 $LD_{50}$  (dermal rabbit) >2000 mg/kg  $LC_{50}$  (inhl rat) >4.3mg/L, 4 hours  $LD_{50}$  (oral rat) >5000 mg/kg

LD<sub>50</sub> (dermal rabbit) 5000 mg/kg

RD<sub>50</sub> 1000 ppm

## **Aspiration hazard**

May be fatal if swallowed and enters airways based on physico-chemical properties of the material.

## **Chronic Exposure:**

Reproductive Toxicity: Not available.

Mutagenicity: Not available.

Teratogenicity: Not available.

d-Limonene:

**Specific Target Organ** 

**Toxicity (STOT)** No end point data.

**Toxicologically Synergistic** 

**Products:** Not available.

**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components.

## 12. Ecological Information

#### 12.1 Toxicity:

**Ecotoxicity:** No information available. **Aquatic Toxicity:** No information available.

**12.2 Persistence and degradability:** Expected to be biodegradable.

**12.3 Bioaccumulation potential:**No information available **12.4 Mobility in soil:**No information available.

**12.5 Results of PBT and vPvB** This product is not, nor does it contain a substance that is a PBT or

Assessment: vPvB.

**12.6 Other adverse effects:** None known.

## 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

## 14. Transport Information

UN Number:
UN Proper shipping name:
Transport hazard class(es):
Not Applicable
Packing group:
Not Applicable

Environmental hazards: None known
Special precautions: None known
TDG: Not Regulated
ICAO/IATA-DGR: Not Regulated
IMDG: Not Regulated
ADR/RID: Not Regulated

## 15. Regulatory Information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

## **USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARA Acute Chronic Fire Pressure Reactive Section 311/312 Reporting No No No No

CERCLA/SARA Sec 302 SARA Sec. 313
Hazardous Substance RQ EHS TPQ Toxic Release

Components are not affected by these Superfund regulations.

NFPA Ratings: Health: 1 Fire: 2

Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

## **European Union**

Components

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

## Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: B3

## **Australia**

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia.

#### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

## 16. Other Information

#### Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

 $LD_{50}$  = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

## **Hazard Statements:**

H227 Combustible liquid

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

Revision Date: January 2, 2015

**Revision Number:** 5

**Supersedes:** October 2, 2014 **Other:** Not Applicable

**Indication of Changes:** Updated supplier address, Section 1.2, 3, 8, 15, 16.

Updated in accordance with the provisions of OSHA 1910.1200 App D and REACH

Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.