## SAFETY DATA SHEET – SET

## **FST-BP Foam Sealant Burst Pack Type FST Kit**

**Product ID numbers:** FST-BP-200, FST-BP-XXX (where XXX is the package code.)

Date Compiled: October 6, 2015



## Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

**Polywater Europe BV** 

Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen Netherlands

Tel: +31 (0)10 2330578 Email: sds@ polywater.com

## **Emergency telephone numbers**

INFOTRAC 1-352-323-3500 (USA)

This product is a kit or a multi-part product with independent components. An SDS for each component is included. Do not separate SDSs.

## Contains

FST-BP-A Foam Sealant Burst Pack Part A SDS FST-BP-B Foam Sealant Burst Pack Part B SDS HP Wipe Cleaning Towelette

Each Kit may or may not contain all SDS components

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

Revision Date: October 5, 2015 Revision Number: rev 1 supersedes --

## SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

# Product Name: FST<sup>™</sup> Foam Sealant Burst Pack FST-BP (Part A)

Product ID numbers: FST-BP-200; FST-BP-XXX (where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Sealant, duct block; two-part material

**List of advices against:** Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

Polywater Europe BV

Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen

Netherlands

Tel: +31 (0)10 2330578 Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

## 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Acute Toxicity, Cat 4 Skin Irritation, Cat 2; H315 Eye Irritation, Cat 2A; H319

Respiratory Sensitization, Cat 1; H334

Skin Sensitization, Cat 1; H317 Carcinogenicity, Cat 2; H351

Target Organ Toxicity (single exposure), Cat 3; H335 Target Organ Toxicity (repeated exposure), Cat 2; H373

2.2 Label elements

**Contains:** Polymeric diphenylmethane diisocyanate; 4,4'-Diphenylmethane diisocyanate (MDI)





Pictograms:

Signal word: Danger

**Hazard Statements:** 

H332 Harmful if inhaled. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer.

Product Name: FST<sup>™</sup> Foam Sealant Burst Pack FST-BP (Part A) Revision Date: October 5, 2015

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated inhalative exposure.

## **Precautionary Statements:**

P260	Do not breathe fumes.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for
P304 + P340	breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308 + P313	If exposed or concerned: Get medical attention.
P362 + P364	Take off contaminated clothing and wash before reuse.

**2.3 Other hazards:** No information available.

## 3. Composition/Information on Ingredients

<u>Component</u> Polymeric diphenylmethane diisocyanate	<u>CAS #</u> 9016-87-9	<u>EC #</u>	<b>Wt. %</b> 30 - 60	GHS/CLP Classification Acute Tox 4, Skin Irrit 2, Eye Irrit 2, Resp Sens1, STOT SE 3, STOT RE 2
4,4'-Diphenylmethane diisocyanate (MDI)	101-68-8	202-966-0	30 - 60	Acute Tox 4, Skin Sens 1, Skin Irrit 2, Eye Irrit 2, Resp Sens1, STOT SE 3, Carc 2, STOT RE 2

### 4. First Aid Measures

### 4.1 Description of first aid measures

**Eye Contact:** Immediately flush eyes with large quantity of water for 15 minutes. Seek medical

attention.

**Skin Contact:** Remove contaminated clothing; flush skin thoroughly with soap and water. If

irritation occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention.

Ingestion (Swallowing): If swallowed, rinse mouth and drink plenty of water. Do not induce vomiting. If

patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person. Do not leave victim unattended. Seek medical attention.

## 4.2 Most important symptoms and effects, both acute and delayed

May cause allergic skin and respiratory reaction. Refer to Section 11 for more information.

### 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

### 5. Firefighting Measures

#### 5.1 Extinguishing media:

Water Fog, Carbon Dioxide, Dry Chemical or Foam.

### 5.2 Special hazards arising from the substance or mixture

## Hazardous decomposition and by-products:

Carbon monoxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapors.

### 5.3 Advice for firefighters

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.

Product Name: FST<sup>™</sup> Foam Sealant Burst Pack FST-BP (Part A) Revision Date: October 5, 2015

#### 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures:

Wear full protective clothing, including appropriate respiratory protection.

## 6.2 Environmental precautions:

Prevent from entering waterways.

## 6.3 Methods materials for containment and cleaning up:

Spills expected to be small quantities. Collect excess material with absorbents or wipe with dry towels. Wash with a dilute ammonia solution.

#### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

## 7. Handling and Storage

## 7.1 Precautions for safe handling

Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

## 7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

## 7.3 Specific end uses

See technical data sheet on this product for further information.

### 8. Exposure Controls / Personal Protection

#### 8.1 Control parameters

## **Exposure limits and recommendations:**

Component Name	Limit	Standard	Source/Note
4,4'-Diphenylmethane diisocyanate (MDI)	0.02 ppm	OSHA TWA	<b>United States</b>
4,4'-Diphenylmethane diisocyanate (MDI)	0.005 ppm	ACGIH TWA	<b>United States</b>
4,4'-Diphenylmethane diisocyanate (MDI)	0.051 mg/m <sup>3</sup>	OEL TWA	NIOSH REL
Polymeric diphenylmethane diisocyanate	0.02 ppm	OSHA TWA	<b>United States</b>

### 8.2 Exposure controls

## Respiratory protection:

Use with adequate ventilation to keep vapor concentration below acceptable limits. Observe OSHA standard 29 CFR 1910-94, 1910.107, 1910.108. Product mixed and used as directed emits less than 0.001 ppm MDI vapor as tested by OSHA 47. Ventilation is not required for standard use. If product is use in a way that ventilation is not adequate, use approved chemical/mechanical filters designed to remove a combination of particulate and organic vapors in open and restricted areas. Use approved airline type respirators or hoods in confined areas. Observe OSHA standard 29 CFR 1910.134.

#### **Protective gloves:**

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include neoprene, butyl rubber, Viton, Buna N, and chlorinated polyethylene.

## Eye protection:

Safety glasses recommended.

## Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

## 9. Physical and Chemical

Product Name: FST<sup>™</sup> Foam Sealant Burst Pack FST-BP (Part A)

## 9.1 Information of basic physical and chemical properties

Appearance: Brown liquid

Odor threshold: Faint, aromatic odor pH: Does not apply

Freezing point: 3°C

Boiling point: 200°C

Flash point: 428°F / 220°C (open cup)

**Evaporation rate:** Not available **Flammability (solid, gas):** Does not apply

Upper/lower flammability or

**explosive limits:** Not available

Vapor pressure: .00016 mm Hg @ 20°C

Vapor density (Air = 1):  $1.22 \text{ g/cm}^3$ Specific gravity (H<sub>2</sub>O = 1):  $1.22 \text{ @ } 25^{\circ}\text{C}$ 

Solubility in water: Reacts

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:> 250°C (1112°F)Decomposition temperature:Not available

**Viscosity:** 200 mPas @ 25°C / 77°F

9.2 Other Information

Volatiles (Weight %): 0%
VOC Content: 0 g/l

## 10. Stability and Reactivity

### 10.1 Reactivity:

Reacts with water, reacts with substances which contain active hydrogen.

## 10.2 Chemical stability:

Stable

## 10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

#### 10.4 Conditions to avoid:

Avoid freezing, high temperatures, flame, high humidity and water contamination.

## 10.5 Incompatible materials:

Water, alcohols, amines, acids, alkalis, metal compounds.

## 10.6 Hazardous decomposition products:

Carbon monoxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapors.

### 11. Toxicological Information

### 11.1 Information on toxicological effects:

## **Acute toxicity**

## Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

## Skin contact:

Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Allergic skin reaction symptoms include redness, swelling, blistering and itching.

#### **Irritation and Sensitization Potential:**

Revision Date: October 5, 2015

**Product Name:** FST<sup>™</sup> Foam Sealant Burst Pack FST-**BP** (Part A) Revision Date: October 5, 2015

Product may be irritating to skin and eyes.

## Inhalation (Breathing):

Material has low vapor pressure and inhalation hazard is expected to be minimal. Vapor exposure may cause irritation of the nose and throat. Symptoms may include burning sensation, coughing and shortness of breath, or other signs of respiratory distress. May cause allergic respiratory reaction below exposure quideline in susceptible individuals.

## Ingestion:

Ingestion may cause irritation of the gastrointestinal tract.

## **Toxicity to Animals:**

4,4'-Diphenylmethane diisocyanate (MDI):  $LD_{50}$  (oral rat) >2,000 mg/kg

LD<sub>50</sub> (dermal rabbit) >9,400 mg/kg

LC<sub>10</sub> (inhl rat) 2.24 mg/m<sup>3</sup>, 1 hour, aerosol form

## **Aspiration Hazard:**

No aspiration hazard expected.

## **Chronic Exposure:**

**Reproductive Toxicity:** Not available. Mutagenicity: Not available. Teratogenicity: Not available.

**Specific Target Organ** 

**Toxicity (STOT)** Contains material which causes damage to the upper respiratory tract.

**Toxicologically Synergistic** 

**Products:** Not available.

This substance contains components identified as IARC Category 3, not

**Carcinogenic Status:** classifiable.

Respiratory/Skin Sensitization

May cause sensitization by inhalation and skin contact..

## 12. Ecological Information

#### 12.1 Toxicity:

## Aquatic Toxicity:

4,4'-Diphenylmethane diisocyanate (MDI):  $LC_{50}$  (96 hr): > 1,000 mg/l Brachydanio rerio (fish)

OECD Guideline 203 static

 $EC_{50}$  (24 hr): > 1,000 mg/l Daphnia magna (invertebrate) 4,4'-Diphenylmethane diisocyanate (MDI):

OECD Guideline 202, part 1 static

4,4'-Diphenylmethane diisocyanate (MDI): EC<sub>50</sub> (72 hr): 1,640 mg/l Green algae (aquatic plants)

OECD Guideline 201 static Elimination information:

12.2 Persistence and degradability: <10% BOD of the ThOD (28d)

(OECD Guideline 302 C, aerobic, activated sludge)

Under test conditions, poorly biodegradable.

12.3 Bioaccumulation potential: Accumulation in organisms is not to be expected.

12.4 Mobility in soil: Adsorption to solid soil phase is not expected

12.5 Results of PBT and vPvB

This product is not, nor does it contain a substance that is a PBT or

Assessment: vPvB.

12.6 Other adverse effects: None known.

## 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

#### 14. Transport Information

Product Name: FST<sup>™</sup> Foam Sealant Burst Pack FST-BP (Part A) Revision Date: October 5, 2015

**UN Number:** Not Listed **UN Proper shipping name:** Not Applicable Transport hazard class(es): Not Applicable Packing group: Not Applicable **Environmental hazards:** None known Special precautions: None known TDG: Not Regulated ICAO/IATA-DGR: Not Regulated IMDG: Not Regulated ADR/RID: Not Regulated

## 15. Regulatory Information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARA	<u>Acute</u>	<b>Chronic</b>	<u>Fire</u>	<u>Pressure</u>	<b>Reactive</b>
Section 311/312 Reporting	Yes	Yes	No	No	No

Components
4,4'-Diphenylmethane diisocyanate (MDI)
Polymeric diphenylmethane diisocyanate
No

CERCLA/SARA Sec 302
Hazardous Substance RQ
Yes (5,000 lbs)
No
No
Yes (1%)
Yes (1%)

NFPA Ratings: Health: 2

Fire: 1
Reactivity: 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

### **European Union**

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

#### Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: Class D, Division 2A

## **Australia**

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia. Product classified as harmful (Xn).

## **15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

### 16. Other Information

## Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration CLP = Classification, Labeling and Packaging Regulation Product Name: FST<sup>™</sup> Foam Sealant Burst Pack FST-BP (Part A) Revision Date: October 5, 2015

STOT = Specific Target Organ Toxicity

 $LD_{50}$  = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

**Revision Date:** October 5, 2015

Revision Number: 1
Supersedes: --

Other: Not Applicable

Indication of Changes: Written in accordance with the provisions of OSHA 1910.1200 App D and REACH

Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

Revision Date: October 5, 2015 Revision Number: rev 1 supersedes --

## SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

## 1.1 Product identifier

# Product Name: FST<sup>™</sup> Foam Sealant Burst Pack FST-BP (Part B)

Product ID numbers: FST-BP-200; FST-BP-XXX (where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Sealant, duct block; two-part material

**List of advices against:** Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

**Polywater Europe BV** 

Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen

Netherlands

Tel: +31 (0)10 2330578 Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Acute Toxicity, Cat 4; H302 Skin Irrit., Cat 2; H315 Eye Irrit., Cat. 2A; H319 Skin Sens., Cat. 1; H317

#### 2.2 Label elements

**Contains:** 2-Propanol,1-chloro-, Phosphate (3:1)



**Pictograms:** 

Signal word: Warning

**Hazard Statements:** 

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

**Precautionary Statements:** 

P261 Avoid breathing fumes.

P270 Do not eat drink or smoke when using this product.

P280 Wear protective gloves, protective clothing and eye protection.

P301 + P312 IF SWALLOWED: Call a doctor if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

**Product Name:** FST<sup>™</sup> Foam Sealant Burst Pack FST-**BP** (Part B)

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P362 + P364 Take off contaminated clothing and wash before reuse.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

Revision Date: October 5, 2015

P338

present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical attention.

**2.3 Other hazards:** No information available.

## 3. Composition/Information on Ingredients

<u>Component</u>	CAS#	EC #	Wt. %	<b>GHS/CLP Classification</b>
Polyether polyol mixture	Proprietary		60 - 100	
2-propanol, 1-chloro-, Phosphate (3:1)	13674-84-5	237-158-7	10 - 30	Acute Tox. 4
Modifiend Isophoronediamine	90530-15-7	292-053-3	0.5 – 1.5	Acute Tox 4 Skin Sens 1 Eye Irrit. 2
Tertiary amine compounds	Proprietary		0.1 - 1	

#### 4. First Aid Measures

## 4.1 Description of first aid measures

Eye Contact: Immediately flush eyes with large quantity of water for 15 minutes. Seek medical

attention.

**Skin Contact:** Remove contaminated clothing; flush skin thoroughly with soap and water. If

irritation occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention.

Ingestion (Swallowing): If swallowed, get medical attention. Do not induce vomiting. If patient is

conscious, wash out mouth with water. Never give anything by mouth to an

unconscious person. Do not leave victim unattended.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

## 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

## 5. Firefighting Measures

## 5.1 Extinguishing media:

Water Fog, Carbon Dioxide, Dry Chemical or Foam.

## 5.2 Special hazards arising from the substance or mixture

## Hazardous decomposition and by-products:

Carbon monoxide, carbon dioxide, phosphorus oxides, silicon dioxide, hydrogen chloride gas.

#### 5.3 Advice for firefighters

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture.

#### 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Wear full protective clothing, including appropriate respiratory protection.

## 6.2 Environmental precautions:

Prevent from entering waterways.

## 6.3 Methods materials for containment and cleaning up:

Spills expected to be small quantities. Collect excess material with absorbents or wipe with dry towels. Wash

Product Name: FST™ Foam Sealant Burst Pack FST-BP (Part B) Revision Date: October 5, 2015

with a dilute ammonia solution.

#### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

## 7. Handling and Storage

#### 7.1 Precautions for safe handling

Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

#### 7.2 Conditions for safe storage, including incompatibilities

Keep containers dry, and away from excessive heat. Keep cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

## 7.3 Specific end uses

See technical data sheet on this product for further information.

#### 8. Exposure Controls / Personal Protection

## 8.1 Control parameters

## **Exposure limits and recommendations:**

Contains no components with established Occupational Exposure Limit (OEL) values.

## 8.2 Exposure controls

## Respiratory protection:

Use with adequate ventilation to keep vapor concentration below acceptable limits.

## Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include neoprene, butyl rubber, Viton, Buna N, and chlorinated polyethylene.

#### Eye protection:

Safety glasses recommended.

## Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

## 9. Physical and Chemical

## 9.1 Information of basic physical and chemical properties

Appearance: Clear to light amber liquid

Odor threshold: Mild amine odor pH: Not available Freezing point: Not available Soiling point: >392°F / >200°C

Flash point: >360°F / >182°C (PMCC)

**Evaporation rate:** Not available **Flammability (solid, gas):** Does not apply

Upper/lower flammability or

explosive limits:Not availableVapor pressure:Not availableVapor density (Air = 1):Not availableSpecific gravity ( $H_2O = 1$ ):Not available

Product Name: FST™ Foam Sealant Burst Pack FST-BP (Part B) Revision Date: October 5, 2015

Solubility in water: Not available

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 0% VOC Content: 0 g/l

## 10. Stability and Reactivity

## 10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability:

Stable

## 10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4 Conditions to avoid:

Avoid freezing, high temperatures, and moisture.

## 10.5 Incompatible materials:

Isocyanates, strong oxidizing agents and strong bases.

## 10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, phosphorus oxides, silicon dioxide, hydrogen chloride gas.

### 11. Toxicological Information

### 11.1 Information on toxicological effects:

### **Acute toxicity**

## Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

## Skin contact:

May cause skin irritation

### Irritation and Sensitization Potential:

Not considered a skin sensitizer.

## Inhalation (Breathing):

May cause respiratory irritation.

#### Ingestion:

Harmful if swallowed.

## **Toxicity to Animals:**

2-propanol, 1-chloro-, Phosphate (3:1) LD<sub>50</sub> (oral rat) 1,500 mg/kg

LD<sub>50</sub> (dermal rabbit) 1,230 mg/kg LC<sub>10</sub> (inhl rat) 5 mg/m<sup>3</sup>, 4 hours

## **Aspiration Hazard:**

No aspiration hazard expected.

#### **Chronic Exposure:**

Reproductive Toxicity: Not available.

Mutagenicity: Not available.

Product Name: FST™ Foam Sealant Burst Pack FST-BP (Part B) Revision Date: October 5, 2015

**Teratogenicity:** Not available.

**Specific Target Organ** 

**Toxicity (STOT)** Not available.

**Toxicologically Synergistic** 

**Products:** Not available.

This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

### 12. Ecological Information

12.1 Aquatic Toxicity: No information available.
 12.2 Persistence and degradability: No information available.
 12.3 Bioaccumulation potential: No information available.
 12.4 Mobility in soil: No information available.

**12.5 Results of PBT and vPvB**This product is not, nor does it contain a substance that is a PBT or

**Assessment:** vPvB.

**12.6 Other adverse effects:** None known.

## 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

## 14. Transport Information

**UN Number:** Not Listed **UN Proper shipping name:** Not Applicable Transport hazard class(es): Not Applicable Packing group: Not Applicable **Environmental hazards:** None known Special precautions: None known TDG: Not Regulated **ICAO/IATA-DGR:** Not Regulated IMDG: Not Regulated ADR/RID: Not Regulated

## 15. Regulatory Information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **USA Federal and State**

**Components** 

All components are listed on the TSCA inventory.

Hazard Categories for SARAAcuteChronicFirePressureReactiveSection 311/312 ReportingYesNoNoNoNo

CERCLA/SARA Sec 302 SARA Sec. 313
Hazardous Substance RQ EHS TPQ Toxic Release

The components of Foam Sealant FST - Part B are not affected by these Superfund regulations.

NFPA Ratings: Health: 2

Fire: 1
Reactivity: 0

**Product Name:** FST™ Foam Sealant Burst Pack FST-**BP** (Part B)

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

## **European Union**

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

### Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: Not Classified.

#### **Australia**

All components are listed on the AICS.

#### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

### 16. Other Information

## Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD<sub>50</sub> = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

**Revision Date:** October 5, 2015

Revision Number: 1 Supersedes: --

Other: Not Applicable

Indication of Changes: Written in accordance with the provisions of OSHA 1910.1200 App D and REACH

Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

Revision Date: October 5, 2015

Revision Date: January 2, 2015 Revision Number: 4, supersedes 3

## **SAFETY DATA SHEET**

## 1. Identification of the substance/mixture and of the company

#### 1.1 Product identifier

# Product Name: Type HP<sup>™</sup> Cleaner/Degreaser Saturated Towel/Wipe Package

Product ID numbers: HP-1, HP-1C, HP-1M,

HP-P158ID, HP-P158IDB, HP-P158IDC, HP-P158IDM, HP-3P158IDS, HP-6P158ID,

HP-P1K, HP-P63, HP-P63C HP-D72, HP-D72C, HP-D72E,

HP-P31212, HP-P369,

HP-T369, HP-T369/S, HP-T369/SC, HP-T369/SH, HP-T369/S-D, HP-T369/S-DC

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Electrical cleaning List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270

Email: sds@polywater.com

**Polywater Europe BV** 

Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen

Netherlands

Tel: +31 (0)10 2330578 Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

### 2. Hazards Identification

## 2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Skin Sens 1 H317 Flam Liq 4 H227

2.2 Label elements

Contains: Petroleum distallates, hydrotreated light; d-Limonene



**Pictograms:** 

Signal word: Warning

**Hazard Statements:** 

H227 Combustible liquid

H317 May cause an allergic skin reaction.

**Precautionary Statements:** 

P210 Keep away from flames and hot surfaces. No smoking.

P280 Wear protective gloves.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local and national regulations.

Notes: Aspiration classification not applied due to the physical form of the product.

**2.3 Other hazards:** No information available.

## 3. Composition/Information on Ingredients

Component	CAS#	EC #	<u>Wt. %</u>	GHS/CLP Classification Asp. Tox. 1 H304;
Petroleum distillates, hydrotreated light	64742-47-8	265-149-8	< 100	EUH066 Skin Irrit. 3 H316; Flam Lig 4 H227
				Flam Liq 3, H226 Skin Irrit 2, H315 Skin Sens 1, H317 Aquatic Chronic 1, H410
d-Limonene	5989-27-5	227-813-5	< 10	Aquatic Acute 1, H400

### 4. First Aid Measures

### 4.1 Description of first aid measures

**Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes

with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

**Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation

occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth. If victim is drowsy or

unconscious, place on the left side with head down. Do not leave victim

unattended. Seek medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

## 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

## 5. Firefighting Measures

### 5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

### 5.2 Special hazards arising from the substance or mixture

## Hazardous decomposition and by-products:

Burning generates CO, CO<sub>2</sub> and smoke. Smoke may be acrid and fumes irritating.

### 5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

#### 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package.

## 6.2 Environmental precautions:

Avoid release to the environment.

## 6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

#### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

## 7. Handling and Storage

## 7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

## 7.3 Specific end uses

See technical data sheet on this product for further information.

## 8. Exposure Controls / Personal Protection

## 8.1 Control parameters

### **Exposure limits and recommendations:**

Component Name	Limit	Standard	Source/Note
Petroleum distillates, hydrotreated light	100 ppm	ACGIH TWA	United States
Petroleum distillates, hydrotreated light	500 ppm	OSHA TWA	United States
Petroleum distillates, hydrotreated light	1200 mg/m <sup>3</sup>	RCP* TWA	ACGIH, Manufacturer
d-Limonene	110 mg/m <sup>3</sup>	DFG** OEL	Germany
		*reciprocal calculation procedure for total hydrocarbor	

<sup>\*\*</sup>deutsche forschungsgemeinschaft, German Research

### 8.2 Exposure controls

## Respiratory protection:

Normal ventilation is adequate. Towelette limits solvent vapor exposure. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Foundation

## **Protective gloves:**

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use

0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material. Maximum wearing time should be determined based on 50 % of the penetration time determined by EN 374 part III.

## Eye protection:

None necessary. Wipe package eliminates splash hazard. Do not allow wipe/towel to directly contact eyes.

## Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

## 9. Physical and Chemical

## 9.1 Information of basic physical and chemical properties (bulk liquid)

**Appearance:** Clear, colorless liquid with a very light citrus scent.

Odor threshold:

pH:

Does not apply

Freezing point:

Solve in the state of the st

Flash point: >140°F (>60.5°C), Closed Cup (PMCC)

**Evaporation rate:** <0.1 (n-butyl acetate = 1) **Flammability (solid, gas):** Not applicable to liquids

Upper/lower flammability or

explosive limits: LEL = 0.7% UEL = 6.1%-7.0% Vapor pressure: <1 mm Hg < 134 Pa @ 20°C

Vapor density (Air = 1): > 1.0Specific gravity (H<sub>2</sub>O = 1): 0.79 Solubility in water: Nil

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 100% VOC Content: 790 g/l

### 10. Stability and Reactivity

### 10.1 Reactivity:

See remaining headings in Section 10.

## 10.2 Chemical stability:

Stable

#### 10.3 Possibility of hazardous reactions:

None known.

### 10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

## 10.5 Incompatible materials :

Strong oxidizing agents.

## 10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

## 11. Toxicological Information

# 11.1 Information on toxicological effects: Acute toxicity

#### Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

#### Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

#### **Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes. It may cause an allergic skin reaction.

## Inhalation (Breathing):

Concentrated petroleum solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

## Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

## **Toxicity to Animals:**

Petroleum distillates,

hydrotreated light: LD<sub>50</sub> (oral rat) >5000 mg/kg

 $LD_{50}$  (dermal rabbit) >2000 mg/kg  $LC_{50}$  (inhl rat) >4.3mg/L, 4 hours

d-Limonene: LD<sub>50</sub> (oral rat) >5000 mg/kg

LD<sub>50</sub> (dermal rabbit) 5000 mg/kg

RD<sub>50</sub> 1000 ppm

#### **Aspiration hazard**

Liquid solvent has an aspiration hazard. This route of exposure is not expected for towelette form.

## **Chronic Exposure:**

Reproductive Toxicity:Not available.Mutagenicity:Not available.Teratogenicity:Not available.

**Specific Target Organ** 

**Toxicity (STOT)** No end point data.

**Toxicologically Synergistic** 

**Products:** Not available.

**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components.

### 12. Ecological Information

## 12.1 Toxicity:

**Ecotoxicity:** No information available. **Aquatic Toxicity:** No information available.

**12.2 Persistence and degradability:** Expected to be biodegradable.

**12.3 Bioaccumulation potential:**No information available **12.4 Mobility in soil:**No information available.

12.5 Results of PBT and vPvB

This product is not, nor does it contain a substance that is a PBT or

**Assessment:** vPvB.

**12.6 Other adverse effects:** None known.

## 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

## 14. Transport Information

**UN Number:** Not Listed **UN Proper shipping name:** Not Applicable Transport hazard class(es): Not Applicable Packing group: Not Applicable **Environmental hazards:** None known Special precautions: None known TDG: Not Regulated **ICAO/IATA-DGR:** Not Regulated IMDG: Not Regulated ADR/RID: Not Regulated

## 15. Regulatory Information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARA	<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>
Section 311/312 Reporting	No	No	Yes	No	No

CERCLA/SARA Sec 302 SARA Sec. 313
Components Hazardous Substance RQ EHS TPQ Toxic Release

Components are not affected by these Superfund regulations.

NFPA Ratings: Health: 1

Fire: 2 Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

## **European Union**

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

#### Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: B3

#### **Australia**

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia. Product classified as harmful (Xn).

#### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

## 16. Other Information

### Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

 $LD_{50}$  = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

#### **Hazard Statements:**

H227 Combustible liquid

H317 May cause an allergic skin reaction.

Revision Date: January 2, 2015

**Revision Number:** 5

**Supersedes:** September 23, 2014 **Other:** Not Applicable

**Indication of Changes:** Section 1, 2, 3, 8, 15, 16 updated. Hazard and precautionary codes adjusted,

additional information on exposure limits. Addition of acronyms and other formatting

changes.

Updated in accordance with the provisions of OSHA 1910.1200 App D and REACH

Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.